

Annex A – SCUBA Equipment and Minimum Specifications

Item	Minimum Specifications
Bouyancy compensator device (BCD)	<ul style="list-style-type: none"> • Large, easy-to-access utility pocket is found on each side of the Wave. • Features 2 stainless steel flat D-rings for all of your accessories. • Right shoulder pull dump with highly visible orange pull bob is easy to locate and use. • Lower rear dump with highly visible orange pull bob is useful for horizontal or head down orientation. • Adjustable chest strap for personal comfort. • Comes in different sizes including 3XS and 2XS.
Wet suit	<ul style="list-style-type: none"> • Full Suit • 3mm Neoprene • Back YKK zipper with Nylon webbing for easy zipping • Flat lock stitched construction with contravention color sewing • Equip with printing knee pad protection • Combination of Black and Orange neoprene
Diving booties	<ul style="list-style-type: none"> • New anatomically correct shaped foot bed and outsole • Asymmetric toe, instep, and heel cap for added protection and durability • Hook & loop zipper lock • Standard neoprene upper with exterior thickness markings • Flexible vulcanized rubber outsole • Four seam (2 front, 2 heel) pattern • Non-corrosive heavy-duty zipper
Frameless mask	<ul style="list-style-type: none"> • Silicone face skirt • One window design • Expanded top-to-bottom viewing window • Tempered glass lens • Adjustable buckle • Black silicone
Snorkel	<ul style="list-style-type: none"> • 100% submersible dry top snorkel with Pivot-Dry technology • Full-flex section and hypoallergenic Silicone mouthpiece for optimum fit and maximum comfort • Easy-clear purge valve • Colors: Blue and Black
Regulator (APEKS AT20)	<p>First Stage:</p> <ul style="list-style-type: none"> • Use the UST first stage. • A balanced, diaphragm design

	<ul style="list-style-type: none"> • 1 HP port and 4 MP ports are available. <p>Second Stage:</p> <ul style="list-style-type: none"> • Pneumatically-balanced second stage results in smooth, easy breathing. • The integrated venture control provides a performance boost at depth while preventing unwanted free flow at the surface. • The Comfort-bite mouthpiece virtually eliminates jaw-fatigue. <p>Octopus:</p> <ul style="list-style-type: none"> • Pneumatically-balanced second stage results in smooth, easy breathing. • The diver has full control of the venture by means of a lever so as to prevent accidental free flow when the octopus is not being used.
Fins	<ul style="list-style-type: none"> • Blade made of two materials of polypropylene with rubber inserts, offering comfort and durability • Anti-slip rubber pads • Quick Release buckles are easy to operate and make exiting the water hassle free. • Ergonomic straps adjust easily, even while wearing thick gloves. • Yellow color great underwater sighting
Pressure gauge (APEKS AT20)	<ul style="list-style-type: none"> • Pressure gauge and depth-gauge in-line • Luminous easy to read dial design • Very compact and lightweight • Depth gauge reads up to 70 meters • Pressure readings up to 400 bar • With standard 32" inches HP Hose
Aluminum cylinder tank with valve	<ul style="list-style-type: none"> • Pressure: 3000 psi (200 bars) • Diameter: 7.3" (18.5 cm) • Weight: 31.5 (14.3 kg) • Height: 25.8" (65.5 cm) • Volume: 80 cubic • Buoyancy Full: -1.7lbs (-771g) • Cylinder Nitrox Ready: Yes, Up to 23.5%

	<ul style="list-style-type: none"> • Valves:— • Material: Chrome Plated Brass, Rubber and Plastic • Type(Yoke, DIN, Convertible): Convertible • Valve Nitrox Ready: Yes, Up to 23.5% • Thread Size: 0.750-14 NPSM • Tank Booth
Belt	<ul style="list-style-type: none"> • Belt webbing 52” ocean diver with plastic buckle
Weights	<ul style="list-style-type: none"> • Lead weights 2lbs.brick
Compressor	<ul style="list-style-type: none"> • Liters / Minute: 235L • Maximum Service Pressure: Final Safety Valve Service Pressure 232 bar / 3,364 psi • Number of Filling Hoses: 2 filling hoses 1.2 m – 3.9 ft length • Filtration: Maxi filter • Condensate Drain: Manual • Lubrication: Splash lubrication • Dimensions (LxWxH): 1000 x 460 x 700 mm (approx.) • Weight: 105 kg – 231 lb • Electric motor driven