Annex B – Bidder's Proposal

Bidder's Business Name	
Business Address	
Tax Identification Number	
Authorized Contact Person	
Contact Details	

## Part 1 – Equipment Details

Item Minimum Specifications		Bidder's Propos	al
		Brand and specification	Unit Price
Bouyancy compensator device (BCD)	<ul> <li>Large, easy-to-access utility pocket is found on each side of the Wave.</li> <li>Features 2 stainless steel flat D-rings for all of your accessories.</li> <li>Right shoulder pull dump with highly visible orange pull bob is easy to locate and use.</li> <li>Lower rear dump with highly visible orange pull bob is useful for horizontal or head down orientation.</li> <li>Adjustable chest strap for personal comfort.</li> <li>Comes in different sizes including 3XS and 2XS.</li> </ul>		•
Wet suit	<ul><li>Full Suit</li><li>3mm Neoprene</li></ul>	•	•

	<ul> <li>Back YKK zipper with         Nylon webbing for         easy zipping</li> <li>Flat lock stitched         construction with         contravention color         sewing</li> <li>Equip with printing         knee pad protection</li> <li>Combination of Black         and Orange neoprene</li> </ul>
Diving booties	<ul> <li>New anatomically correct shaped foot bed and outsole</li> <li>Asymmetric toe, instep, and heel cap for added protection &amp;durability</li> <li>Hook &amp; loop zipper lock</li> <li>Standard neoprene upper with exterior thickness markings</li> <li>Flexible vulcanized rubber outsole</li> <li>Four seam (2 front, 2 heel) pattern</li> <li>Non-corrosive heavyduty zipper</li> </ul>
Frameless mask	<ul> <li>Silicone face skirt</li> <li>One window design</li> <li>Expanded top-to-bottom viewing window</li> <li>Tempered glass lens</li> <li>Adjustable buckle</li> <li>Black silicone</li> </ul>
Snorkel	100% submersible dry top snorkel with Pivot-Dry technology     Full-flex section and hypoallergenic Silicone

	mouthpiece for optimum fit and maximum comfort • Easy-clear purge valve • Colors: Blue and Black
Regulator (APEKS AT20)	First Stage:  • Use the UST first stage.  • A balanced, diaphragm design  • 1 HP port and 4 MP ports are available.
	<ul> <li>Pneumatically-         balanced second stage         results in smooth, easy         breathing.</li> </ul>
	The integrated venture control provides a performance boost at depth while preventing unwanted free flow at the surface.
	The Comfort-bite     mouthpiece virtually     eliminates jaw-fatigue.
	Octopus:
	Pneumatically-     balanced second stage     results in smooth, easy     breathing.
	The diver has full control of the venture by means of a lever so as to prevent accidental free flow when the octopus is not being used.

Pressure gauge (APEKS AT20)	Blade made of two materials of polypropylene with rubber inserts, offering comfort and durability  Anti-slip rubber pads  Quick Release buckles are easy to operate and make exiting the water hassle free.  Ergonomic straps adjust easily, even while wearing thick gloves.  Yellow color great underwater sighting  Pressure gauge and depth-gauge in-line.  Luminous easy to read dial design  Very compact and lightweight;  Depth gauge reads up to 70 meters	
	Depth gauge reads up	
Aluminum cylinder tank with valve	<ul> <li>Pressure: 3000 psi (200 bars)</li> <li>Diameter: 7.3" (18.5 cm)</li> <li>Weight: 31.5 (14.3 kg)</li> <li>Height: 25.8" (65.5 cm)</li> <li>Volume: 80 cubic</li> </ul>	

	<ul> <li>Buoyancy Full: -1.7lbs         (-771g)</li> <li>Cylinder Nitrox Ready:         Yes, Up to 23.5%</li> <li>Valves:—-</li> <li>Material: Chrome         Plated Brass, Rubber         and Plastic</li> <li>Type(Yoke, DIN,         Convertible):         Convertible</li> <li>Valve Nitrox Ready:         Yes, Up to 23.5%</li> <li>Thread Size: 0.750-14         NPSM</li> <li>Tank Booth</li> </ul>		
Belt	<ul> <li>Belt webbing 52"         ocean diver with         plastic buckle</li> </ul>	•	•
Weights	Lead weights 2lbs.brick	•	•
	•	•	
	•	Amount per set	

# Subtotal 1: P (Amount per set) x six (6) set = P

### Additional Equipment:

Additional Equip	inche.		
One (1) unit	Liters / Minute: 235L	•	
Compressor			
	<ul> <li>Maximum Service</li> </ul>		
	Pressure: Final Safety		
	Valve Service Pressure		
	232 bar / 3,364 psi		
	<ul> <li>Number of Filling</li> </ul>		
	Hoses: 2 filling hoses		
	1.2 m – 3.9 ft length		
	<ul> <li>Filtration: Maxi filter</li> </ul>		

	Condensate Drain:     Manual
	Lubrication: Splash     lubrication
	• Dimensions (LxWxH): 1000 x 460 x 700 mm (approx.)
	• Weight: 105 kg – 231 lb
	Electric motor driven
One (1) unit underwater camera	TG5 Olympus and casing

#### Total:

- Subtotal 1 (6 sets SCUBA) = P\_\_\_\_\_

- Total Equipment Cost = P

## Part 2 – Delivery, Testing and Commissioning - Description of equipment delivery and on-site testing and commissioning.

- Delivery mode Describe how equipment will be delivered to the WBA Dive Center, Maluso, Basilan; or alternately through the ZSCMST Dive Center, Zamboanga City.
- How much is the delivery cost? P
- Testing Briefly describe how equipment will be tested and commissioned at site.

## Part 3 – After Sales Support - Describe after sales support in terms, warranty, replacement, technical service support and nearest on-call authorized technician.

- Warranty Describe what is covered in your warranty for these equipment and how these maybe replaced.
- Technical support Is there nearest on-call authorized technician to service these equipment?